

## THERMOSTATIC MIXING VALVE SCHEDULE

TAG	BASIS OF DESIGN		DESIGN FLOW (GPM)	FLOW RANGE (GPM)	MAX. P.D. AT DESIGN FLOW	HW SYSTEM TEMPERATURES		CONNECTION SIZES		NOTES
	MANUFACTURER	MODEL				INLET	OUTLET	INLET	OUTLET	
TMV-1	LEONARD	NV-300-LF-2PS-LC	170	0.25 - 170	10 PSI	160°F	120°F	4"	4"	
TMV-2	ACORN CONTROLS	SFMV-4-T-OB-CWB-ITG	35	0.5 - 70.7	10 PSI	160°F	140°F	1-1/2"	1-1/2"	
TMV-3	ACORN CONTROLS	ST7069-BVS-OTG	4	0.5 - 5.7	10 PSI	125°F	103°F	VARIABLES	VARIABLES	2
TMV-4	ACORN CONTROLS	ST70-38-MB	1	0.25 - 1.9	10 PSI	120°F	103°F	VARIABLES	VARIABLES	2
TMV-5	ACORN CONTROLS	ET72-1-BVS-OTG-DRV	28.7	2.0 - 45.0	20 PSI	120°F	85°F	1-1/2"	1-1/2"	1
1. PROVIDE THERMOSTATIC MIXING VALVE ASSEMBLY WITH LOCKABLE, STAINLESS STEEL, WALL MOUNTED CABINET AND T/P GAUGES ON INLETS AND OUTLET. 2. REFER TO PLANS FOR SIZES.										